



Please follow the enclosed steps to change the special head setting on your printer.

1. Depress both the **MENU** and **CHOICES** buttons while turning on the printer. Keep both buttons depressed until **FACTORY MENU** appears in the LCD window or the display starts scrolling through different topics.
2. Using the **MENU** button scroll down to the **SPECIAL HEAD?**.
3. Using the **CHOICE** button select the head setting you want. Once you have done this press the **TEST** button. The display will show **EXIT AND SAVE**, press the **TEST** button again and the printer should reset itself.

NO	No special head, RADJW set to 3.25" or RADJ4 set to 4" or ADJ4
ON P1	DUAL & SINGLE PATH PRINTER ONLY (fixed path)
ON P2	DUAL PATH PRINTER ONLY on path #2 (fixed path)
ON BOTH	DUAL PATH PRINTER ONLY on both paths (fixed path)
REV ADJ2 P1	DUAL & SINGLE PATH PRINTER WITH RADJW paper guide set to 2"
REV ADJ2 P2	DUAL PATH PRINTER WITH RADJW paper guide set to 2" on path #2
REV ADJ2 BOTH	DUAL PATH PRINTER WITH REV RADJW paper guides set to 2" on both paths
REV ADJ2.5 P1	DUAL & SINGLE PATH PRINTER WITH RADJW paper guide set to 2.50"
REV ADJ2.5 P2	DUAL PATH PRINTER WITH RADJW paper guide set to 2.50" on path #2
REV ADJ2.5 BOTH	DUAL PATH PRINTER WITH REV RADJW paper guides set to 2.50" on both paths
REV ADJ2.7 P1	DUAL & SINGLE PATH PRINTER WITH RADJW paper guide set to 2.70"
REV ADJ2.7 P2	DUAL PATH PRINTER WITH RADJW paper guide set to 2.70" on path #2
REV ADJ2.7 BOTH	DUAL PATH PRINTER WITH REV RADJW paper guides set to 2.70" on both paths
REV ADJ3 P1	DUAL & SINGLE PATH PRINTER WITH RADJW paper guide set to 3"
REV ADJ3 P2	DUAL PATH PRINTER WITH RADJW paper guide set to 3" on path #2
REV ADJ3 BOTH	DUAL PATH PRINTER WITH REV RADJW paper guides set to 3" on both paths
REV ADJ2.125 P1	DUAL & SINGLE PATH PRINTER WITH RADJW paper guide set to 2.125"
REV ADJ2.125 P2	DUAL PATH PRINTER WITH RADJW paper guide set to 2.125" on path #2
REV ADJ2.125 BTH	DUAL PATH PRINTER WITH REV RADJW paper guides set to 2.125" on both paths
REV ADJ3.25 P1	DUAL & SINGLE PATH PRINTER WITH RADJ4 paper guide set to 3.25"
REV ADJ3.25 P2	DUAL PATH PRINTER WITH RAD4 paper guide set to 3.25" on path #2
REV ADJ3.25 BTH	DUAL PATH PRINTER WITH REV RAD4 paper guides set to 3.25" on both paths

Set to: 

If the printer doesn't have a LCD display then it may be changed via the computer the printer is connected to. The CHANGE SPECIAL HEAD SETTING section of the Lemur user manual (www.bocasystems.com/documents/lemur_manual.pdf) provides download procedures.